



PRODUCT SPECIFICATIONS

VINYL WALLCOVERINGS

ARTIST CANVAS, CABRETTA, CANVAS, LUSTER,
MACHE, MATTE, MYSTICAL, PIQUE, PLASTER, PUEBLO,
SAND BLAST, SUEDE

PHYSICAL PROPERTIES

Product Weight: 20 oz. per lineal yd., (13oz. per sq. yd.) Vinyl
Weight: 17 oz. per lineal yd.
Fabric Weight: 3 oz. per lineal yd.
Thickness: 0.015 to 0.030 in.
*depending on texture
Fabric: Poly-Cotton Osnaburg or Polyester Nonwoven *depending
on texture

BREAKING STRENGTHS, LBS. FORCE

Machine Direction-warp:
*Exceeds Type II minimum of 50 lbs. Cross
Machine Direction-fill:
*Exceeds Type II minimum of 55 lbs.

TEARING STRENGTH, SCALE

Machine Direction-warp:
*Exceeds Type II minimum of 25lbs.
Cross Machine Direction-fill:
*Exceeds Type II minimum of 25 lbs.
COLD CRACK RESISTANCE @ 20°F No
change

HEAT AGING (7 DAYS @ 158°F)

*Does not become stiff, brittle, discolored, or show loss of
grain

SPECIFICATIONS / TESTING / CERTIFICATION

Federal Specification:
*CCC-408-D,C,B,A *Type II *Class A CFFA
Specification:
*CFFA-W-101-D *Type II *Class A

FIRE TESTING

ASTM-E84 Tunnel Test Class A
NFPA286 Corner Burn Test Class A
NFPA265 Corner Burn Test Class A
BS476 Part 6&7
*Meets or exceeds requirements for flame spread, smoke
developments and flashover.

MOLD/MILDEW/BACTERIAL RESISTANCE

ASTM-G21 Specifications:
Passed all requirements of CCCW-408-D

ENVIRONMENT

NYC MEA: Register
*Cadmium and Lead Free Formulation